



DYRC-CP-RL

CLEVEREVAC DYNAMIC GREEN & RED X EXIT SIGN



Dynamic LEDs Sequencing Arrow



Illuminated Red X with Side Flashing Red LED's

PRODUCT INFORMATION					
Part Number	DYRC-CP-RL				
MIC	UKA02550060001				
Description	CLP Premium CleverEVAC Dynamic Green & Red X EXIT sign, with Volt Free (VF) & 24V interface for ON/OFF activation of Dynamic Green & Red X Enhancement				
Construction	PC/ABS body with PC diffuser				
Mounting	Ceiling / Wall mounted single sided				
Dimensions L x W x H	367mm x 72mm x 214mm				
Weight	2.0kg				
Operating Mode	Maintained – Sequencing arrows or illuminated Red X with side flashing Red LED's activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode				
Testing System	N/A – Manual Test Switch				
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent current limited constant voltage				
Diffuser	Pictograph, 2 Elements (Running Man and Arrow LEFT)				
Lamp(s)	LED panel, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	1.5 Watts (Standby), 8.0 Watts (Max)				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"> Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts 				
Luminaire Classification	<table border="1" style="display: inline-table;"> <tr> <td>X</td> <td>1</td> <td>AG</td> <td>180</td> </tr> </table>	X	1	AG	180
X	1	AG	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
8002921	8002921 PCA:CCF-Pro #CT10142-L9

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice