



DYRC-CP-RR-HVG

CleverEvac Dynamic Red X Exit, Surface Mount, CLP, Zoneworks Hive, Running Man Arrow Right, Single Sided



Dynamic LEDs Sequencing Arrow

Illuminated Red X with Side Flashing Red LEDs

PRODUCT INFORMATION

Part Number	DYRC-CP-RR-HVG
MIC	UKA0000006901
Description	CleverEvac Dynamic Green Exit, Surface Mount, CLP, Zoneworks Hive, Running Man Arrow Right, Single Sided
Construction	PC/ABS body with PC diffuser
Mounting	Ceiling / Wall mounted single sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.0kg
Operating Mode	Maintained – Sequencing arrows or illuminated Red X with side flashing Red LED's activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode
Testing System	Zoneworks XT Hive (RF) 2.4GHz
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, 2 Elements (Running Man and Arrow Right)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Supply Current	0.081A
Power Factor	0.41
Power Consumption	1.8 Watts (Standby), 8.3 Watts (Max)
Inrush Current (Peak/Duration)	17.4A/132 μ s
Earth Leakage	0.352mA
Viewing Distance	30m
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Rated Emergency Duration	180 minutes
Luminaire Classification	X 1 AGF 180
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550231	Battery
8003025	LED Strip
8002927	Emergency Driver
8003330	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order