

DYRC-CP-RRCLEVEREVAC DYNAMIC GREEN & RED X EXIT SIGN





Dynamic LEDs Sequencing Arrow



Illuminated Red X with Side Flashing Red LED's

PRODUCT INFORMATION						
Part Number	DYRC-CP-RR					
MIC	UKA02550020001					
Description	CLP Premium CleverEVAC Dynamic Green & Red X EXIT sign, with Volt Free (VF) 24V interface for ON/OFF activation of Dynamic Green & Red X Enhancement					
Construction	PC/ABS body with PC diffuser					
Mounting	Ceiling / Wall mounted single sided					
Dimensions L x W x H	367mm x 72mm x 214mm					
Weight	2.0kg					
Operating Mode	Maintained – Sequencing arrows or illuminated Red X with side flashing Red LED's activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode					
Testing System	N/A - Manual Test Switch					
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics					
Charging Method	Intelligent current limited constant voltage					
Diffuser	Pictograph, 2 Elements (Running Man and Arrow RIGHT)					
Lamp(s)	LED panel, 100,000 hours					
Operating Voltage	220-240V AC; 50Hz					
Power Consumption	1.5 Watts (Standby), 8.0 Watts (Max)					
Viewing Distance	30m					
Rated Emergency Duration	180 minutes					
IP Rating	IP20					
Operating temperature	0°C to 40°C					
Protection	 Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts 					
Luminaire Classification	Х	1	AG	180		
Conformity	BS EN 60598-2-22, BS 5266					

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
8002921	8002921 PCA:CCF-Pro #CT10142-L9

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

