

DYRC-CP-RU-HVG

CleverEvac Dynamic Red X Exit, Surface Mount, LP, Zoneworks XT Hive, Running Man Arrow Up, Single Sided









Illuminated Red X with Side Flashing Red LED's

PRODUCT INFORMATION		
Part Number	DYRC-CP-RU-HVG	
MIC	UKA02850160001	
Description	CleverEvac Dynamic Green Exit, Surface Mount, CLP, Zoneworks XT Hive, Running Man Arrow Up, Single Sided	
Construction	PC/ABS body with PC diffuser	
Mounting	Ceiling / Wall mounted single sided	
Dimensions L x W x H	367mm x 72mm x 214mm	
Weight	2.0kg	
Operating Mode	Maintained – Sequencing arrows or illuminated Red X with side flashing Red LED's activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode	
Testing System	Zoneworks XT Hive (RF) 2.4GHz	
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics	
Charging Method	Intelligent current limited constant voltage	
Diffuser	Pictograph, 2 Elements (Running Man and Arrow Left)	
Lamp(s)	LED panel, 100,000 hours	
Operating Voltage	220-240V AC; 50Hz	
Power Consumption	1.8 Watts (Standby), 8.3 Watts (Max)	
Viewing Distance	30m	
Rated Emergency Duration	180 minutes	
IP Rating	IP20	
Operating temperature	0°C to 40°C	
Inrush Current (Max)	17.4A<132 µs	
Earth Leakage	0.352mA	
IP Rating	IP20	
Operating Temperature	0°C to 40°C	
Rated Emergency Duration	180 minutes	
Protection	 Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) 	
Luminaire Classification	X 1 AGF 180	
Conformity	BS EN 60598-2-22, BS 5266	





DYRC-CP-RU-HVGCleverEvac Dynamic Red X Exit, Surface Mount, LP, Zoneworks XT Hive, Running Man Arrow Up, Single Sided

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550230	Battery
8003025	LED Strip
8002927	Emergency Driver
8003330	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

