



## DYRC-CP-RU

### CLEVEREVAC DYNAMIC GREEN & RED X EXIT SIGN



Dynamic LEDs Sequencing Arrow



Illuminated Red X with Side Flashing Red LED's

PRODUCT INFORMATION					
Part Number	DYRC-CP-RU				
MIC	UKA02550030001				
Description	CLP Premium CleverEVAC Dynamic Green & Red X EXIT sign, with Volt Free (VF) & 24V interface for ON/OFF activation of Dynamic Green & Red X Enhancement				
Construction	PC/ABS body with PC diffuser				
Mounting	Ceiling / Wall mounted single sided				
Dimensions L x W x H	367mm x 72mm x 214mm				
Weight	2.0kg				
Operating Mode	Maintained – Sequencing arrows or illuminated Red X with side flashing Red LED's activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode				
Testing System	N/A – Manual Test Switch				
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent current limited constant voltage				
Diffuser	Pictograph, 2 Elements (Running Man and Arrow UP)				
Lamp(s)	LED panel, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	1.5 Watts (Standby), 8.0 Watts (Max)				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"> <li>Battery overvoltage &amp; overcurrent protection</li> <li>Battery deep discharge protection</li> <li>Supply voltage polarity reversal protection</li> <li>Battery short-circuit protection (charging will resume upon removal of fault)</li> <li>Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts</li> </ul>				
Luminaire Classification	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="padding: 2px 10px;">X</td> <td style="padding: 2px 10px;">1</td> <td style="padding: 2px 10px;">AG</td> <td style="padding: 2px 10px;">180</td> </tr> </table>	X	1	AG	180
X	1	AG	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
8002921	8002921 PCA:CCF-Pro #CT10142-L9

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice