DYRC-UP-CM-RD



CleverEvac Dynamic Red X Exit, Ceiling Mount, CLP, Running Man Arrow Down, Single Sided







PRODUCT INFORMATIO	n
Part Number	DYRC-UP-CM-RD
MIC	UKA02550220002
Description	CleverEvac Dynamic Red X Exit, Ceiling Mount, CLP, Running Man Arrow Down, Single Sided
Construction	PC/ABS Body with PC Diffuser and Metal Enclosure
Mounting	Ceiling Mount, Single-sided
Dimensions L x W x H	391mm x 90mm x 257mm
Weight	5.9 kg
Operating Mode	Maintained – Sequencing Inward Green LEDs or Illuminated Red X with Side Flashing Red LED's Activated on VF/24V Input Trigger and Capable of Being Activated in Power-on and Battery-backed Mode. Dynamic Green Default Set to Activate Upon Mains Power Fail.
Testing System	Manual
Battery	Lithium Iron Phosphate, 3.2V 3200mAh Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Single-sided Pictograph, (Running Man with Arrow Down)
Lamp(s)	LED Panel, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.7W (Standby), 8.7W (Max)
Inrush Current (Max)	15.9<37 μs
Earth Leakage	0.375mA
IP Rating	IP20
Operating Temperature	0°C to 40°C
Viewing Distance	30m
Protection	 Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts
Luminaire Classification	X 1 AG 180
Conformity	BS EN 60598-2-22, BS 5266
Compliance Markings	₽₽ CE

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1553250	Battery
1553050	Battery
UKM02570110002	Emergency Driver Pack

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice, and suitable application of the products.

