



DYRC-UP-RL-HVG

CleverEvac Dynamic Red X Exit, Recessed Mount, LP, Zoneworks
XT Hive, Running Man Arrow Left, Single Sided



PRODUCT INFORMATION

Part Number	DYRC-UP-RL-HVG
MIC	AUA02950200001
Description	CleverEvac Dynamic Red X Exit, Recessed Mount, LP, Zoneworks XT Hive, Running Man Arrow Left, Single Sided. Dynamic Green Default Set to Activate Upon Mains Power Fail
Construction	PC/ABS Body with PC Diffuser and Metal Enclosure
Mounting	Recessed Mount, Single-sided
Dimensions L x W x H	385mm x 67mm x 257mm
Weight	3.3kg
Operating Mode	MAINTAINED: Sequencing inward green LEDs or illuminated Red X with side flashing red LED's. Activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode. Dynamic Green Default Set to Activate Upon Mains Power Fail.
Testing System	Zoneworks XT HIVE (RF) 2.4GHz
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Single-sided Pictograph, Two Elements (Running Man with Arrow Right)
Lamp(s)	LED Panel, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.0W (Standby), 9.0W (Max)
Inrush Current (Max)	15.9A @ 140μS
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0 = D2.5, C90=E8
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550250	Battery
8002178	LED Strip
AUM02970170001 DYRC-UP-CKIT-HVG	Emergency Driver
8003560	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order