



DYRC-UP-WM-RL

CleverEvac Dynamic Red X Exit, Wall Mount, LP, Running Man Arrow Left, Single Sided



PRODUCT INFORMATION

Part Number	DYRC-UP-WM-RL
MIC	AUA02550700001
Description	LP Premium CleverEVAC Dynamic Green & Red X Blade Exit Sign, with Volt Free (VF) & 24V Interface for ON/OFF Activation of Dynamic Green & Red X Enhancement. Dynamic Green Default Set to Activate Upon Mains Power Fail.
Construction	PC/ABS Body with PC Diffuser and Metal Enclosure
Mounting	Wall Mount, Single-sided
Dimensions L x W x H	391mm x 90mm x 257mm
Weight	5.9 kg
Operating Mode	Maintained – Sequencing Inward Green LEDs or Illuminated Red X with Side Flashing Red LED's Activated on VF/24V Input Trigger and Capable of Being Activated in Power-on and Battery-backed Mode. Dynamic Green Default Set to Activate Upon Mains Power Fail.
Testing System	Manual
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Single-sided Pictograph, Two Elements (Running Man with Arrow Left)
Lamp(s)	LED Panel, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.7W (Standby), 8.7W (Max)
Inrush Current (Max)	15.9A @ 140uS
Earth Leakage	0.345mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=C8, C90=C32, C180=E4, C270=C32
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550250	Battery
AUM02570030001 DYRC-UP-CKIT	Emergency Driver Pack

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice, and suitable application of the products.