



## DYRC-UP-WM-RR

CleverEvac Dynamic Red X Exit, Wall Mount, LP  
Running Man Arrow Right, Single Sided



### PRODUCT INFORMATION

Part Number	DYRC-UP-WM-RR
MIC	AUA00000015001
Description	CleverEvac Dynamic Red X Exit, Wall Mount, LP, Running Man Arrow Right, Single Sided
Construction	PC/ABS Body with PC Diffuser and Metal Enclosure
Mounting	Wall Mount, Single-sided
Dimensions L x W x H	391mm x 90mm x 257mm
Weight	5.9 kg
Operating Mode	Maintained Sequencing Inward Green LEDs or Illuminated Red X with Side Flashing Red LED's. Activated on VF/24V Input Trigger and capable of being activated in power-on and battery-backed mode. Dynamic green default set to activate upon mains power fail.
Testing System	Manual
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Single-sided Pictograph, Two Elements (Running Man with Arrow Right)
Lamp(s)	LED Panel, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.7W (Standby), 8.7W (Max)
Inrush Current (Peak/Duration)	15.9A / 140µs
Earth Leakage	0.345mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0,C180=E4, C90,C270=C32
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550250	Battery
80500461 and 8003550-MOD	LED Assembly
AUM02570030001 DYRC-UP-CKIT	Emergency Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order