



## DYRL-CP-R-HV

CleverEvac Dynamic Red X Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, Running Man, Single Sided



Dynamic LEDs Sequencing Inwards



Illuminated Red X with Side Flashing Red LED's

### PRODUCT INFORMATION

Part Number	DYRL-CP-R-HV
MIC	AUA01850030001
Description	CleverEvac Dynamic Red X Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, Running Man, Single Sided with Volt Free (VF) & 24V Interface for ON/OFF Activation of Dynamic Green & Red X Enhancement.
Construction	PC/ABS Body with PC Diffuser
Mounting	Ceiling / Wall Mounted Single-sided
Dimensions L x W x H	367mm x 214mm x 80mm
Weight	2.0kg
Operating Mode	Maintained – Sequencing Arrows or Illuminated Red X with Side Flashing Red LED's Activated on VF/24V Input Trigger and Capable of Being Activated in Power-on and Battery-backed Mode. Dynamic Green Default Set to Activate Upon Mains Power Fail.
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Pictograph, Single element (Running Man)
Lamp(s)	LED Panel, 100,000 Hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.5W (Standby), 9.0W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =E1.6 C <sub>90</sub> =E1.25
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
8002925	Driver Pack

**Disclaimer:** Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.