



## DYRL-CP-RL-HVG

CleverEvac Dynamic Red X Exit, Surface Mount, L10 Nanophosphate,  
Zoneworks XT Hive 2.4GHz, Running Man Left, Single Sided



Dynamic LEDs Sequencing Arrow



Illuminated Red X with Side Flashing  
Red LED's

### PRODUCT INFORMATION

Part Number	DYRL-CP-RL-HVG
MIC	AUA01950080001
Description	CleverEvac Dynamic Red X Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Running Man Arrow Left, Single Sided, with Volt Free (VF) & 24V interface for ON/OFF activation of Dynamic Green & Red X Enhancement
Construction	PC/ABS body with PC diffuser
Mounting	Ceiling / Wall mounted single sided
Dimensions L x W x H	367mm x 214mm x 80mm
Cut-Out	N/A
Weight	2.0kg
Operating Mode	Maintained – Sequencing inward green LEDs or illuminated Red X with side flashing Red LED's activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, Single element (Running Man Arrow Left)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.5 Watts (Standby), 9.0 Watts (Max)
Inrush Current (Max)	TBD
Earth Leakage	0.327mA
IP Rating	IP20
IK Rating	N/A
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E1.6 C90=E1.25
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	Battery
8003025	LED Strip
8002927	Driver Pack
8003560	HVG Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.