



## DYRL-CP-RL

CleverEvac Dynamic Red X Exit, Surface Mount, L10 Nanophosphate, Running Man Arrow Left, Single Sided



Dynamic LEDs Sequencing Arrow



Illuminated Red X with Side Flashing Red LED's

### PRODUCT INFORMATION

Part Number	DYRL-CP-RL			
MIC	UKA00000005701			
Description	CleverEvac Dynamic Red X Exit, Surface Mount, L10 Nanophosphate, Running Man Arrow Left, Single Sided			
Construction	PC/ABS body with PC diffuser			
Mounting	Ceiling / Wall mounted single sided			
Dimensions L x W x H	367mm x 72mm x 214mm			
Weight	2.0kg			
Operating Mode	Maintained - Sequencing Arrows or Illuminated Red X with Side Flashing Red LED's Activated on VF/24V Input Trigger and Capable of Being Activated in Power-on and Battery-backed Mode. Dynamic Green Default Set to Activate Upon Mains Power Fail			
Testing System	Manual Test			
Battery Type & Manufacturer	Lithium Nanophosphate, 3.3V 5000mAh			
Charging Method	Intelligent current limited constant voltage			
Diffuser	Pictograph, 2 Elements (Running Man and Arrow Left)			
Lamp(s)	LED panel, 100,000 hours			
Operating Voltage	220-240V AC; 50Hz			
Supply Current	0.081A			
Power Factor	0.41			
Power Consumption	1.5 Watts (Standby), 8.0 Watts (Max)			
Inrush Current (Peak/Duration)	17.4A/132µs			
Earth Leakage	0.338mA			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
Luminaire Classification	X	1	AG	180
Compliance Marking	UK CA CE			
Conformity	BS EN 60598-2-22, BS 5266			

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	Battery
8003048, 8003025	LED Panel
8002927	Emergency Driver

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice