




DYRL-CP-RR

CleverEvac Dynamic Red X Exit, Surface Mount, L10 Nanophosphate, Running Man Arrow Right, Single Sided



Dynamic LEDs Sequencing Arrow



Illuminated Red X with Side Flashing Red LED's

PRODUCT INFORMATION

Part Number	DYRL-CP-RR
MIC	AUA01550150001
Description	CleverEvac Dynamic Red X Exit, Surface Mount, L10 Nanophosphate, Running Man Arrow Right, Single Sided
Construction	PC/ABS Body with PC Diffuser
Mounting	Ceiling / Wall Mounted Single-sided
Dimensions L x W x H	367mm x 214mm x 80mm
Weight	2.0kg
Operating Mode	Maintained: Sequencing Arrows or Illuminated Red X with Side Flashing Red LED's Activated on VF/24V Input Trigger. Capable of Being Activated in Power-on and Battery-backed Mode. Dynamic Green Default Set to Activate Upon Mains Power Fail.
Testing System	N/A - Manual Test Switch
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Pictograph, Two Elements (Running Man and Arrow Right)
Lamp(s)	LED Panel, 100,000 Hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.5W (Standby), 9.0W (Max)
Inrush Current (Peak/Duration)	17.4A / 132µS
Earth Leakage	0.352mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E1.6 C ₉₀ =E1.25
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	Battery
8003025	LED Assembly
8002927	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order