



DYRL-UP-CM-R-HVG

CleverEvac Dynamic Red X Exit, Ceiling Mount, L10 Nanophosphate,
Zoneworks XT Hive 2.4GHz, Running Man, Single Sided



PRODUCT INFORMATION

Part Number	DYRL-UP-CM-R-HVG
MIC	AUA01950040001
Description	CleverEvac Dynamic Red X Exit, Ceiling Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Running Man, Single Sided
Construction	PC/ABS Body with PC Diffuser and Metal Enclosure
Mounting	Ceiling Mount
Dimensions L x W x H	391mm x 90mm x 257mm
Weight	5.9kg
Operating Mode	Maintained – Sequencing inward green LEDs or illuminated Red X with side flashing red LED's activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode. From 1st of April 2022 Dynamic GREEN default set to activate upon mains power fail.
Testing System	Zoneworks XT HIVE (RF), 2.4GHz
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, Single element (Running Man)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.0 Watts (Standby), 9.0 Watts (Max)
Inrush Current(Peak/Duration)	15.9A/140µs
Earth Leakage	0.295mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D5, C90,C270=C25, C180=E6.3
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530250	Batter
8003560	Hive Node
AUM01970160001 DYRL-UP-CKIT-HVG	EM Driver

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.