



DYRL-UP-CM-RR-HVG

CleverEvac Dynamic Red X Exit, Ceiling Mount, L10
Nanophosphate, Zoneworks Hive, Running Man Arrow Right,
Single Sided



PRODUCT INFORMATION	
Part Number	DYRL-UP-CM-RR-HVG
MIC	AUA00000017301
Description	CleverEvac Dynamic Red X Exit, Ceiling Mount, L10 Nanophosphate, Zoneworks Hive, Running Man Arrow Right, Single Sided
Construction	PC/ABS Body with PC Diffuser and Metal Enclosure
Mounting	Ceiling Mount, Single-sided
Dimensions L x W x H	391mm x 90mm x 257mm
Weight	5.9 kg
Operating Mode	Maintained Sequencing Inward Green LEDs or Illuminated Red X with Side Flashing Red LED's. Activated Over the XT HIVE Network or on VF/24V Input Trigger. Capable of Being Activated in Power-on and Battery-backed Mode. Dynamic Green Default Set to Activate Upon Mains Power Fail.
Testing System	Zoneworks HIVE (RF) 2.4GHz
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Single-sided Pictograph, Two Elements (Running Man with Arrow Right)
Lamp(s)	LED Panel, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.0W (Standby), 9.0W (Max)
Supply Current	0.093A
Power Factor	0.44
Inrush Current (Peak/Duration)	15.9A/140µs
Earth Leakage	0.295mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D5, C90=C25, C180=E6.3, C270=C25
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530250	Battery
AUM01970160001	Emergency Driver
8003560	Node

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.
The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.