

## **DYRL-UP-CM-RU**

## CLEVEREVAC DYNAMIC GREEN & RED X BLADE EXIT SIGN





Part Number	DYRL-UP-CM-RU					
MIC	UKA01550100001					
Description	L10 Optimum CleverEVAC Dynamic Green and Red X Blade EXIT sign, with Volt Free (VF) & 24V interface for ON/OFF activation of Dynamic Green & Red X Enhancement					
Construction	PC/ABS body with Acrylic diffuser					
Mounting	Ceiling Mount					
Dimensions L x W x H	391mm x 90mm x 257mm					
Weight	5.9kg					
Operating Mode	Maintained – Sequencing inward green LEDs or illuminated Red X with side flashing red LED's activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode					
Testing System	N/A - Manual Test Switch					
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics					
Charging Method	Intelligent current limited constant voltage					
Diffuser	Single sided Pictograph, two elements (Running Man with Arrow Up)					
Lamp(s)	LED panel, 100,000 hours					
Operating Voltage	220-240V AC; 50Hz					
Power Consumption	1.7 Watts (Standby), 8.7 Watts (Max)					
Viewing Distance	30m					
Rated Emergency Duration	180 minutes					
IP Rating	IP20					
Operating temperature	0°C to 40°C					
Protection	<ul> <li>Battery overvoltage &amp; overcurrent protection</li> <li>Battery deep discharge protection</li> <li>Supply voltage polarity reversal protection</li> <li>Battery short-circuit protection (charging will resume upon removal of fault)</li> <li>Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts</li> </ul>					
Luminaire Classification	Х	1	AG	180		
Conformity	BS EN 60598	3-2-22. BS 5	266			

REPLACEMENT PARTS			
PART NUMBER	DESCRIPTION		
1530250	BATT:L10 3.3V 5AH. SBS		
1530050	BATT:L10 3.3V 2.5AH 70mm lead, no BRKT		
UKM01570010001 DYRL-UP-CKIT	Dynamic Red, UB Pro, Control Only, L10		

<sup>\*</sup>Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

