



DYRL-UP-R-HVG

CleverEvac Dynamic Green & Red X Blade Exit, Recessed Mount,
L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Running Man, Single Sided



PRODUCT INFORMATION

Part Number	DYRL-UP-R-HVG
MIC	AUA01950020001
Description	CleverEvac Dynamic Green and Red X Blade Exit, Recessed Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Running Man, Single Sided. With Volt Free (VF) & 24V interface for ON/OFF activation of Dynamic Green & Red X Enhancement
Construction	PC/ABS body with PC diffuser
Mounting	Recessed, Single-sided
Dimensions L x W x H	385mm x 67mm x 257mm
Weight	3.3kg
Operating Mode	Maintained – Sequencing inward green LEDs or illuminated Red X with side flashing red LED's activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, Single element (Running Man)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.0 Watts (Standby), 9.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E2.5 C90=E8
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530250	BATTERY:L10 3.3V 5AH. SBS
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.