



DYRL-UP-RR-HVG

CleverEvac Dynamic Green & Red X Blade Exit, Recessed Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Running Man Right, Single Sided



PRODUCT INFORMATION

Part Number	DYRL-UP-RR-HVG
MIC	AUA01950050001
Description	CleverEvac Dynamic Green and Red X Blade Exit, Recessed Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Running Man Right, Single Sided. With Volt Free (VF) & 24V interface for ON/OFF activation of Dynamic Green & Red X Enhancement
Construction	PC/ABS body with PC diffuser
Mounting	Recessed, Single-sided
Dimensions L x W x H	385mm x 67mm x 257mm
Weight	3.3kg
Operating Mode	Maintained – Sequencing inward green LEDs or illuminated Red X with side flashing red LED's activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, Single element (Running Man)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.0 Watts (Standby), 9.0 Watts (Max)
Earth Leakage	0.35
Inrush Current	15.9A
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E2.5 C90=E8
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530250	Battery
2310251	LED Strip
AUM01970160001 DYRL-UP-CKIT-HVG	Driver Pack
8003560	HIVE Node