



DYRL-UP-R

CLEVEREVAC DYNAMIC GREEN & RED X BLADE EXIT SIGN



PRODUCT INFORMATION	
Part Number	DYRL-UP-R
MIC	AUA01550040001
Description	L10 Optimum CleverEVAC Dynamic Green and Red X Blade EXIT sign, with Volt Free (VF) & 24V interface for ON/OFF activation of Dynamic Green & Red X Enhancement. From 1st of April 2022 Dynamic GREEN default set to activate upon mains power fail.
Construction	PC body with PC diffuser
Mounting	Recessed, Single-sided
Dimensions L x W x H	385mm x 67mm x 257mm
Weight	3.3kg
Operating Mode	Maintained – Sequencing inward green LEDs or illuminated Red X with side flashing red LED's activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode. From 1st of April 2022 Dynamic GREEN default set to activate upon mains power fail.
Testing System	Manual
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, Single element (Running Man)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.7 Watts (Standby), 9.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E2.5 C90=E8
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530250	BATTERY:L10 3.3V 5AH. SBS

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.