DYRL-UP-WM-RU-HVG

CleverEvac Dynamic Red X Exit, Recessed Mount, L10 Nanophosphate, Zoneworks HIVE, Running Man Arrow Up, Single Sided





PRODUCT INFORMATION	
Part Number	DYRL-UP-WM-RU-HVG
MIC	UKA00000019801
Description	CleverEvac Dynamic Red X Exit, Recessed Mount, L10 Nanophosphate, Zoneworks HIVE, Running Man Arrow Up, Single Sided
Construction	PC/ABS body with Acrylic diffuser, No Charge Indicator LED, No Branding On Decal, No Visible Product Label, Cover Plate and Blade Trim painted in RAL9016
Mounting	Recessed, Single Sided
Dimensions L x W x H	385mm x 67mm x 257mm
Weight	3.3kg
Operating Mode	Maintained – Sequencing inward green LEDs or illuminated Red X with side flashing red LED's activated on VF/24V input trigger. Capable of being activated in power-on and battery-backed mode
Testing System	Zoneworks HIVE (RF) 2.4GHz
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Diffuser	Single sided Pictograph, two elements (Running Man with Arrow Up)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Factor	0.427
Supply Current	0.09A
Power Consumption	2.0 Watts (Standby), 9.0 Watts (Max)
Inrush Current (Peak/Duration)	TBA
Earth Leakage	TBA
Viewing Distance	30m
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0˚C to 40˚C
Luminaire Classification	X | 1 | AFG | 180
Conformity	BS EN 60598-2-22, BS 5266
Compliance Marking	UKCA CE

DYRL-UP-WM-RU-HVG

CleverEvac Dynamic Red X Exit, Recessed Mount, L10 Nanophosphate, Zoneworks HIVE, Running Man Arrow Up, Single Sided

REPLACEMENT PARTS	
PART NUMBER	**DESCRIPTION**
1533250	Battery
1533050	Battery
UKM01870180002	Emergency Driver
8003330	Node

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products. The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

DYRL-UP-WM-RU-HVG

CleverEvac Dynamic Red X Exit, Recessed Mount, L10 Nanophosphate, Zoneworks HIVE, Running Man Arrow Up, Single Sided