



# EBULK

CLEVERTRONICS EL BULKLITE  
WEATHERPROOF EMERGENCY LIGHT



PRODUCT INFORMATION	
Part Number	EBULK
MIC	INS03520010001
Description	EL Bulklite Weatherproof Emergency Light
Construction	Base Material: Polycarbonate Diffuser Cover Material: Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	346mm x 132mm x 86mm
Weight	1.0kg
Operating Mode	Non-Maintained – Can be adjusted using test switch
Testing System	Manual
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO <sub>4</sub> ), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	LED module, 50,000 hours at Ta 30°, 6500K, Ra>80
Diffuser	EXIT decals available separately
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.4Watts (Standby), 2.7Watts (Maintained Standby), 4.0Watts (Max)
Total lumen output	218lm (Emergency) 218lm (Maintained)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.



# EBULK

## CLEVERTRONICS EL BULK-LITE WEATHERPROOF EMERGENCY LIGHT

### PRODUCT INFORMATION

Rated Emergency Duration	180 minutes				
IP Rating	IP65				
IK Rating	IK08				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li></ul>				
Luminaire Classification (UK)	<table border="1"><tr><td>X</td><td>0</td><td>AD</td><td>180</td></tr></table>	X	0	AD	180
X	0	AD	180		
AS2293 Classification (ANZ)	C0=D32, C90=D20				
Applicable Standards	BS EN 60598-2-22, BS 5266, AS/NZS3820, CISPR15, AS/NZS2293.3				
Compliance Marking					

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560160	BATT:EcoLith 3.2V 3.0Ah 170mm lead,NoBKT
8050800	LED: HWSUB: CT10754-D2 Bulkhead LED Strip - 2835 EL
8002989	DRIVER: PCA: EL Bulkhead CT10614-L2 6C80

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.