



## ECLLED-LI

CLEVERTRONICS ECONOMY LITHIUM CIRCLITE



PRODUCT INFORMATION	
Part Number	ECLLED-LI
MIC	AUC03510030001
Description	Economy Lithium Circlite Emergency Luminaire
Construction	Polycarbonate Base, Opal Acrylic Diffuser
Mounting	Surface Mount
Dimensions L x W x H	348mm (Diameter) x 100mm (Height)
Weight	2.3kg
Operating Mode	Sustained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Driver	CFL-D13
Lamp(s)	LED Panel Array (30,000hrs), 4000K (default), CRI Ra> 80
Operating Voltage	240V AC; 50Hz (double insulated)
Total lumen output	1417lm
Power Consumption	0.6 Watts (Standby), 16 Watts (Max)
IP Rating	IP44
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D32 C90=D32
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1560280	Battery
8003070	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.