



## EJELED-40-LI

CLEVERTRONICS ECONOMY LITHIUM JUMBO LED EXIT  
UNIVERSAL MOUNT



PRODUCT INFORMATION	
Part Number	EJELED-40-LI
MIC	AUA03510060001
Description	Economy Lithium Jumbo Emergency Exit
Construction	Powder Coated Metal Frame with Acrylic Diffuser
Mounting	Wall, Ceiling single-Sided & Ceiling Double-Sided
Dimensions L x W x H	630mm x 100mm x 320mm
Weight	6.9kg
Operating Mode	Can be toggled between maintained and non-maintained mode by pressing the test button 5 times within a 4 second period - default setting is maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x High intensity LED, surface mounted onto a replaceable lamp bar - 50,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	2.9 Watts (Standby), 4.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D6.3 C90=E3.2
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1560156	BATT:EcoLith 3.2V 3.0Ah 200mm lead, BKT
8003055	PCA: EJELED-LI LED Strip #CT10648-D2
AUM03570020001 EJELED-40-LI-CKIT-85	Eco LI Jumbo LED Exit, Control Kit, 85mA

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.