



## EJELED-40-LI

Economy Lithium Jumbo Emergency Exit Universal Mount



### PRODUCT INFORMATION

Part Number	EJELED-40-LI
MIC	AUA03510060003
Description	Economy Lithium Jumbo Emergency Exit Universal Mount
Construction	Powder Coated Metal Frame with Acrylic Diffuser
Mounting	Wall, Ceiling single-Sided & Ceiling Double-Sided
Dimensions L x W x H	630mm x 100mm x 320mm
Weight	6.9kg
Operating Mode	Can be toggled between maintained and non-maintained mode by pressing the test button 5 times within a 4 second period - default setting is maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x High intensity LED, surface mounted onto a replaceable lamp bar – 50,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	3.6 Watts (Standby), 4.8 Watts (Max)
Earth Leakage	0.013mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D8, C90=E4, C180=E3.2, C270=E4
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560280, 3730043	Battery
805-00085	LED Panel
AUM00000007501	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.