



ELIFE-X-LI-SM-WP

CLEVERTRONICS EL LIFELIGHT IP65 WEATHERPROOF
SURFACE MOUNT EMERGENCY



PRODUCT INFORMATION

Part Number	ELIFE-X-LI-SM-WP
MIC	AUD03520010001
Description	Economy Lithium Lifelight, Weatherproof, Surface Mounted Emergency Light
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	247mm x 129mm x 51mm
Ceiling Cut-Out	N/A
Minimum Ceiling Depth	N/A
Weight	0.8kg
Operating Mode	Non-Maintained
Testing System	Manual Test Switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4W (Standby) 1.3W (Max)
Inrush Current (Max)	9A
Earth Leakage	N/A
IP Rating	IP65
IK Rating	IK08
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560160	Battery
8050174	LED Head Assembly
8002986	EM Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.