



## EPIC-1200-LP-HVG

Epic 1200mm Diffused Emergency Batten, LP, Switchable Colour & Output, Zoneworks XT Hive 2.4GHz



### PRODUCT INFORMATION

Product Code	EPIC-1200-LP-HVG
MIC	AUB02910030001
Description	Epic 1200mm Diffused Emergency Batten, LP, Switchable Colour & Output, Zoneworks XT Hive 2.4GHz
Switchable Colour CCT	3000K / 4000K / 5700K (default 4000K)
Switchable Output	High / Low (default High)
Construction	Powder Coated Sheet Metal Base, Co-extruded IP40 PC Diffuser Assembly, PC End Caps
Mounting	Surface Mount
Dimensions LxWxH (mm)	1203x72x78
Weight (kg)	1.8
Operating Mode	SUSTAINED
Testing System	Zoneworks HIVE
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Co-extruded IP40 PC Diffuser Assembly
Driver / Ballast	LED Driver - 40W Stallion, SP2
Lamp(s)*	Dual LED strip module, 3000K warm white, 5700K cool white, >50,000hr life, Ra>80 L70/B50 Ta 40°C; Reported >54,000hr, Projected 158,000hr L80/B50 Ta 40°C; Reported >54,000hr, Projected 99,000hr
Supply Voltage	220-240V~ 50Hz
Power Factor	0.90 @ High Output
Supply Current	180mA +/- 20mA
Inrush Current (Max)	30.8A, <100µs
Earth Leakage	0.35mA-0.45mA
Total lumen output	4673 lm (129 lm/W) @ default 4000K High Output, standby lamp on (refer to table below for details)
Power Consumption	36.2W @ default 4000K High Output, standby, lamp on (refer to table below for details)
Operating Temperature	1°C to 40°C
IP Rating	IP20
Impact Rating	IK03
LED MacAdam Step (SDCM)	4
AS2293 Classification	C0=D63 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	



## EPIC-1200-LP-HVG

Epic 1200mm Diffused Emergency Batten, LP, Switchable Colour & Output, Zoneworks XT Hive 2.4GHz



### REPLACEMENT PARTS

COMPONENT	PART NUMBER & DESCRIPTION
1330088	240V Driver
AUM02970210002 CLIFE-PRO-CKIT-HVGEXTA-NP	Driver Pack
8050570	240V LED Strip
1550230	Battery

Power Consumption & Lumen Output	High Output (700mA)			
	Max Charge, Lamp On	Standby Charge, Lamp On	Standby Charge, Lamp Off	Lumen Output
3000K	40.2W	37.9W	0.7W	4227 lm
4000K (DEFAULT)	38.5W	36.2W	0.7W	4673 lm
5700K	39.7W	37.4W	0.7W	4447 lm

Power Consumption & Lumen Output	Low Output (350mA)			
	Max Charge, Lamp On	Standby Charge, Lamp On	Standby Charge, Lamp Off	Lumen Output
3000K	21.1W	18.8W	0.7W	2277 lm
4000K	20.6W	18.3W	0.7W	2439 lm
5700K	20.9W	18.6W	0.7W	2413 lm

\*The projected value has been calculated by extrapolation of the LM80 data using the Energy Star Calculator

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order