



FBKLED-WW-DD-WHT

240V Bunkalite IP65 Weatherproof Luminaire with Warm White LED and Dali Driver, White



PRODUCT INFORMATION

Part Number	FBKLED-WW-DD-WHT
MIC	AUS04620060002
Description	240V Bunkalite IP65 Weatherproof Luminaire with Warm White LED and Dali Driver, White
Construction	Base Material: Die-cast Aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	Diameter 360mm, Depth 145mm
Weight	4.5kg
Diffuser	Polycarbonate
LED Driver	Tridonic LCA 17W 250–700mA one4all SC PRE (DALI)
Lamp(s)	LED module, 3,000K Warm White, 50,000h life, Ra>80
Operating Voltage	220–240V~ 50Hz
Supply Current	0.062A
Power Factor	0.94
Total Lumen Output	1868lm @ 137.3lm/W
Power Consumption	13.6 Watts
IP Rating	IP65
Impact Rating	IK10
Operating Temperature	0°C to 40°C
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1330160	240V Driver
801-00048	LED Strip

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order