



FBS4LED-DIF

CLEVERTRONICS 240V ODYSSEY QUANTUM LED DIFFUSED BATTEN



PRODUCT INFORMATION

Part Number	FBS4LED-DIF
MIC	AUB04610020001
Description	240V Odyssey Quantum LED diffused batten
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface mount
Dimensions L x W x H	1238mm x 120mm x 108mm
Weight	3.0kg
Diffuser	Prismatic
Driver / Ballast	50W 700mA, XZ-STB50, 50,000hr
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	4585lm @ 123lm/W
Power Consumption	37 Watts
IP Rating	IP20
Operating Temperature	1°C to 40°C
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1330059	LED XZ Driver - 50w 700mA, 30-54V
8002695	PCA:LED Strip 8S6P, ALS-13-840-0-02-B

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.