



## FBS4LED-LO-DIF-DD

Odyssey Diffused 1200mm Batten, DALI Driver, Low Output



PRODUCT INFORMATION	
Part Number	FBS4LED-LO-DIF-DD
MIC	AUB04610120001
Description	Odyssey Diffused 1200mm Batten, DALI Driver, Low Output
Material	Powder Coated Steel Body with Acrylic Prismatic Diffuser and PC/ABS End Caps
Mounting	Surface Mount
Dimensions	1238mm x 120mm x 108mm
Weight	3kg
Driver	LED Driver - LCA 50w 350-1050mA, one4all
Lamp(s)	LED Strip Module, 4,000K Natural White, 50,000h Life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Total Lumen Output	2438lm @128lm/W
Power Consumption	19 Watts
IP Rating	IP20
LED MacAdam Step (SDCM)	5
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1330056	LED Driver
8002695	LED Assembly

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order