



FCLLED-MS

CLEVERTRONICS 240V LED CIRCLITE WITH MICROWAVE SENSOR



PRODUCT INFORMATION	
Part Number	FCLLED-MS
Description	240V LED Circlite with Microwave Sensor
Construction	Polycarbonate Base and Opal Acrylic Diffuser
Mounting	Surface mount
Dimensions	348mm (Diameter) x 100mm (Height)
Diffuser	Opal Acrylic
Lamp(s)	LED panel array (30,000 hours), 4000K, Ra>80
Total Lumen Output	1340lm @90lm/W
Operating Voltage	250V AC; 50Hz (double insulated)
Power Consumption	1.6W (Standby) 14.9 Watts (MAX)
IP Rating	IP44
Operating Temperature	1°C to 40°C
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

DESCRIPTION OF MICROWAVE SENSOR

- Detection angle: 30-150°
- Detection range: 12-18M(diameter),adjustable
- Time setting: 10sec-30min,adjustable
- Light-control: 5-100LUX,adjustable
- Mounting height: Max.12M

