

FORM-16-REC-CM-L10-ESC

Form 16M Exit, Recessed Ceiling Mount, L10 Nanophosphate, Clevertest Plus, All Pictograms, Double Sided, Escape Route Illumination, Brushed Aluminium Frame



| Product Code | FORM-16-REC-CM-L10-ESC | |
|---------------------------|---|--|
| MIC | AUA01310740001 | |
| Description | Form 16M Exit, Recessed Ceiling Mount, L10 Nanophosphate, Clevertest Plus, All Pictograms, Double Sided, Escape Route Illumination, Brushed Aluminium Frame | |
| Construction | PCM Box with PC/Aluminium Extrusion Blade | |
| Diffuser | Polycarbonate | |
| Mounting | Recessed Ceiling Mount, Double Sided | |
| Electrical Connection | Push Terminal | |
| Viewing Distance | 16m | |
| Operating Mode | Maintained | |
| Testing System | Clevertest Plus | |
| Battery | Lithium Nanophosphate, 3.3V 2500mAh | |
| Charging Method | Intelligent Current Limited Constant Voltage | |
| Lamp(s)* | 18 x LED, >100,000hrs (AS/NZS2293.3 LSL=73Y/00M) | |
| Supply Voltage | 220-240V~ 50Hz | |
| Power Factor | 0.28 (Standby, Maintained), 0.42 (Max) | |
| Supply Current | 19.91 (Standby, Maintained), 35.60 (Max) mA | |
| Inrush Current (Max) | 10A<144 μs | |
| Earth Leakage | 0.35mA | |
| Power Consumption | 1.2W (Standby), 3.3W (Max) | |
| Operating Temperature | 1 ºC - 40ºC | |
| IP Rating | IP20 | |
| Impact Rating | IK03 | |
| Escape Route Illumination | 2 x Directional & Rotational Lens | |
| AS2293 Classification | Refer to next page | |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 | |
| Compliance Marking | & | |






FORM-16-REC-CM-L10-ESC

Form 16M Exit, Recessed Ceiling Mount, L10 Nanophosphate, Clevertest Plus, All Pictograms, Double Sided, Escape Route Illumination, Brushed Aluminium Frame

| Twin Rotating Emergency Lens – Orientation | | СО | C90 | C180 | C270 |
|--|--|-------|-----|------|-------|
| Perpendicular to the blade | | D32 | C10 | D32 | C12.5 |
| Parallel to the blade | | C12.5 | D32 | E5 | D32 |
| Mixed one perpendicular, one parallel to the blade) | | D25 | D20 | D20 | D25 |

| DIMENSIONS | | | | |
|----------------------------|----------------|--|--|--|
| Blade Assembly (LxWxH mm) | 220 x 18 x 110 | | | |
| Body/Box (LxWxH mm) | 225 x 63 x 53 | | | |
| Cover Plate (LxW mm) | 245 x 85 | | | |
| Rod/Cable (LxDIAø mm) | N/A | | | |
| Cut-Out (LxW mm) | 230 x 65 | | | |
| Minimum Ceiling Depth (mm) | 70 | | | |
| Weight (kg) | 0.75 | | | |



| REPLACEMENT PARTS | | |
|-------------------|------------------|--|
| PART NUMBER | DESCRIPTION | |
| 1530050 | Battery | |
| AUM1370530001 | Emergency Driver | |
| 8011954 | LED Strip | |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications, or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

