



FORM-16-REC-WM-LP-ESC

Form 16M Exit, Recessed Wall Mount, LP, Clevertest Plus, Emergency, All Pictograms, Single Sided






PRODUCT INFORMATION	
Product Code	FORM-16-REC-WM-LP-ESC
MIC	AUA02310700001
Description	Form 16M Exit, Recessed Wall Mount, LP, Clevertest Plus, Emergency, All Pictograms, Single Sided
Construction	PCM Box with PC/Aluminium Extrusion Blade
Diffuser	Polycarbonate
Mounting	Recessed Wall Mount, Single Sided
Electrical Connection	Push Terminal
Viewing Distance	16m
Operating Mode	Maintained
Testing System	Clevertest Plus
Lamp(s)*	18 x LED, >100,000hrs (AS/NZS2293.3 LSL=73Y/00M)
Escape Route Illumination	2 x Directional & Rotational Lens
LED Lifetime	> 100,000hrs (AS/NZS2293.3 LSL=73Y/00M)
Supply Voltage	220-240V~ 50Hz
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Power Consumption	1.2W (Standby), 3.3W (Max)
Power Factor	0.28 (Standby, Maintained), 0.42 (Max)
Supply Current	19.91 (Standby, Maintained), 35.60 (Max) - (mA)
Inrush Current (Max)	10A<144μs
Earth Leakage	0.325mA
Operating Temperature	1 °C - 40°C
IP Rating	IP20
Impact Rating	IK03
AS2293 Classification	Refer to next page
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking	



FORM-16-REC-WM-LP-ESC


Form 16M Exit, Recessed Wall Mount, LP, Clevertest Plus,
Emergency, All Pictograms, Single Sided

AS/NZS 2293.1:2018 CLASSIFICATION

Twin Rotating Emergency Lens – Orientation		C0	C90	C180	C270
Perpendicular to the blade		D32	C10	D32	C12.5
Parallel to the blade		C12.5	D32	E5	D32
Mixed one perpendicular, one parallel to the blade)		D25	D20	D20	D25

DIMENSIONS

Blade Assembly (LxWxH mm)	220 x 18 x 110
Body/Box (LxWxH mm)	220 x 52 x 100
Cover Plate (LxW mm)	N/A
Rod/Cable (LxDIAø mm)	N/A
Cut-Out (LxW mm)	200x 90
Minimum Ceiling Depth (mm)	65
Weight (kg)	0.75



REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
8051000	Emergency LED Panel
AUM00000001001 CLEDDRV2CH-VV-2C170-6C30-15-CKIT	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications, or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order