



FVP4LED-P-DD

Argonaut Vandal Resistant 1200mm Weatherproof Batten, DALI Driver



PRODUCT INFORMATION

Catalogue Number	FVP4LED-P-DD
MIC	AUB04630050002
Description	Argonaut Vandal Resistant 1200mm Weatherproof Batten, DALI Driver
Construction	Pressure Die-Cast, Low Copper Aluminium Alloy Body with Powder Coat Paint Finish Removable Gear Tray and Replaceable LED Modules
Mounting	Surface Mount
Dimensions L x W x H	1320mm x 140mm x 120mm
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws, LSZH
Driver / Ballast	Tridonic LCA 50W 350-1050mA ONE4ALL
Lamp(s)	LED strip module, 4000K, (CRI) Ra>80 L70/B50 Ta 40°C; LM80 Report >60,000hr, Projected 184,000hr L80/B20 Ta 40°C; LM80 Report >60,000hr, Projected 100,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr
LED MacAdam Step (SDCM)	3
Operating Voltage	240V AC; 50Hz
Total lumen output	5632 lm @ 143lm/W
Power Consumption	39.3 Watts
IP Rating	IP66
Operating Temperature	0°C to 40°C
Impact Rating	IK11
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1330056	240V Driver
8002755	LED Strip

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.