



FVP4LED-P-DD

Argonaut Vandal Resistant 1200mm Weatherproof Batten, DALI-2 Driver



PRODUCT INFORMATION

Catalogue Number	FVP4LED-P-DD
MIC	UKB00000018901
Description	Argonaut Vandal Resistant 1200mm Weatherproof Batten, DALI-2 Driver
Construction	Pressure Die-Cast, Low Copper Aluminium Alloy Body with Powder Coat Paint Finish Removable Gear Tray and Replaceable LED Modules
Mounting	Surface Mount
Dimensions L x W x H	1320mm x 140mm x 120mm
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws, LSZH
Driver / Ballast	Tridonic LCA 50W 350-1050mA ONE4ALL
Lamp(s)	LED strip module, 4000K, (CRI) Ra>90 L70/B50 Ta 40 °C: Reported >120,000h, Projected 226,600h L80/B20 Ta 40 °C: Reported >120,000h, Projected 134,600h L90/B10 Ta 40 °C: Reported 63,600h, Projected 63,600h
LED MacAdam Step (SDCM)	3
Operating Voltage	240V AC; 50Hz
Total lumen output	5632 lm @ 143lm/W
Power Consumption	39.3 Watts
Operating Temperature	0 °C to 40 °C
IP Rating	IP66
Impact Rating	IK11
Conformity	BS EN IEC 60598-2-1, BS EN IEC 55015, BS EN IEC 61547, BS EN IEC 61000-3-2, BS EN IEC 61000-3-3
Compliance Marking	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1330056	Mains Driver
8012110	LED Strip

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.