



GLIDER-LP-HVG

Glider Exit, Recessed Ceiling Mount, LP, Zoneworks XT Hive,
All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	GLIDER-LP-HVG
MIC	AUA00000000401
Description	Glider Exit, Recessed Ceiling Mount, LP, Zoneworks XT Hive, All Pictograms, Single or Double Sided
Construction	PC/ABS body with PC diffuser
Mounting	Recessed Ceiling, Double Sided
Dimensions L x W x H	365mm x 95mm x 203mm
Weight	1.9kg
Operating Mode	Maintained
Testing System	Zoneworks XT Hive (RF), 2.4GHz
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All pictograph directional inserts included in the box
Lamp/s	12 x Samsung LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.1 Watts (Max)
Supply Current	43mA +/- 3mA
Inrush Current (Peak/Duration)	25.3A / 94µs
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E3.2, C90=E3.2, C180=E2.5, C270=E3.2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550150	Battery
8051190	LED Assembly
800-00016	Emergency Driver
800-00022	Hive Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order