



GLIDER-LP-HVG

Glider Exit, Recessed Ceiling Mount, CLP, Zoneworks HIVE, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	GLIDER-LP-HVG
MIC	UKA00000007601
Description	Glider Exit, Recessed Ceiling Mount, CLP, Zoneworks HIVE, All Pictograms, Single or Double Sided
Material	PC/ABS body with PC diffuser
Mounting	Recessed Ceiling, Single or Double Sided
Dimensions	365mm x 95mm x 203mm
Cut-Out	345mm x 65mm
Minimum Depth	60mm
Weight	1.9kg
Operating Mode	Maintained
Testing System	Zoneworks HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Samsung LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.3 Watts (Standby), 4.0 Watts (Max)
Supply Current	0.051A ±3mA
Power Factor	0.29
Inrush Current (Peak/Duration)	25.3A / 94µs
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	0°C to 40°C
Rated Emergency Duration	180 minutes
Viewing Distance	30m
Compliance Marking	UK CE
Luminaire Classification	X 1 AFG 180
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553150	Battery
800-00091	Emergency Driver
8051190	Emergency LED Panel
800-00101	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order