GLIDER-LP

Glider Exit, Recessed Ceiling Mount, CLP, Clevertest Plus, All Pictograms, Single or Double Sided, White

PRODUCT INFORMATION	
Part Number	GLIDER-LP
MIC	UKA00000007501
Description	Glider Exit, Recessed Ceiling Mount, CLP, Clevertest Plus, All Pictograms, Single or Double Sided, White
Material	PC/ABS body with PC diffuser
Mounting	Recessed Mount, Double Sided
Dimensions	Overall: 365mm x 95mm x 203mm Blade: 315mm x 156mm x 9mm
Cut-out	345mm x 65mm
Minimum Depth	60mm
Weight	1.2kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not Activated By Default)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Samsung LED, LED Lifetime: >100,000 hrs
Operating Voltage	220-240V~ 50Hz
Power Consumption	2.0 Watts (Standby), 3.7 Watts (Max)
Supply Current	TBC
Power Factor	0.29
Inrush Current (Peak/Duration)	TBC
Earth Leakage	TBC
IP Rating	IP20
Operating Temperature	0˚C to 40˚C
Rated Emergency Duration	180 Minutes
Viewing Distance	30m
Compliance Marking	UK CA CE
Protection Class	⧈
Luminaire Classification	X | 1 | AG | 180
Conformity	BS EN 60598-2-22, BS 5266

GLIDER-LP

Glider Exit, Recessed Ceiling Mount, CLP, Clevertest Plus, All Pictograms, Single or Double Sided, White

REPLACEMENT PARTS	
PART NUMBER	**DESCRIPTION**
1553150	Battery
800-00091	Emergency Driver
8051190	LED Panel
N/A	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order