GLIDER-SM-LP-BLK

Glider Exit, Surface Mount, CLP, Clevertest Plus, All Pictograms, Single or Double Sided, Black

PRODUCT INFORMATION

Part Number	GLIDER-SM-LP-BLK
MIC	UKA00000049201
Description	Glider Exit, Surface Mount, CLP, Clevertest Plus, All Pictograms, Single or Double Sided, Black
Material	PC/ABS body with PC diffuser
Mounting	Surface Mount, Double Sided
Dimensions	Overall: 341mm x 60mm x 215mm Blade: 315mm x 156mm x 9mm Body Box: 341mm x 60mm x 60mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not Activated By Default)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Samsung LED, LED Lifetime: >100,000 hrs
Operating Voltage	220-240V~ 50Hz
Power Consumption	2.0 Watts (Standby), 3.7 Watts (Max)
Supply Current	TBC
Power Factor	0.29
Inrush Current (Peak/Duration)	TBC
Earth Leakage	TBC
IP Rating	IP20
Operating Temperature	0˚C to 40˚C
Rated Emergency Duration	180 Minutes
Viewing Distance	30m
Compliance Marking	UK CA CE
Protection Class	⧈
Luminaire Classification	X | 1 | A G | 1 8 0
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553150	Battery
800-00089	Emergency Driver
805-00041	LED Panel
N/A	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order