



## GLIDER-SM-LP-D2-BLK

Glider Exit, Surface Mount, LP, DALI-2 Emergency, All Pictograms, Single or Double Sided, Black



### PRODUCT INFORMATION

Part Number	GLIDER-SM-LP-D2-BLK
MIC	AUA00000011301
Description	Glider Exit, Surface Mount, LP, DALI-2 Emergency, All Pictograms, Single or Double Sided, Black
Construction	PC/ABS body with PC diffuser
Mounting	Surface Mount, Double Sided
Dimensions L x W x H	341mm x 60mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All pictograph directional inserts included in the box
Lamp/s	12 x Samsung LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Supply Current	43mA +/- 3mA
Power Factor	0.22
Power Consumption	1.4 Watts (Standby), 3.1 Watts (Max)
Inrush Current (Peak/Duration)	25.3A / 94µs
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E3.2, C90=E3.2, C180=E2.5, C270=E3.2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550150	Battery
800-00014	Emergency Driver
805-00041	LED Panel
800-00027	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order