



LBLLED-REC-WM-D2-RR

Boxlite Recessed Wall Mounted Exit, L10 Nanophosphate, DALI-2 Emergency, Stainless Steel Trim, Running Man Arrow Right



PRODUCT INFORMATION

Part Number	LBLLED-REC-WM-D2-RR
MIC	AUA01211770001
Description	Boxlite Recessed Wall Mounted Exit, L10 Nanophosphate, DALI-2 Emergency, Stainless Steel Trim, Running Man Arrow Right
Construction	Body - Folded sheet steel Trim Finish - Standard: Stainless Steel
Mounting	Recessed Wall
Dimensions L x W x H	350mm x 200mm (Trim) x 81mm (wall depth)
Cut-Out	325mm x 180mm x 81mm
Weight	2.9kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage charger
Diffuser	Running Man Arrow Right
Lamp(s)	6 x high intensity, low energy LED, surface mounted onto a replaceable lamp bar – 100,000 hour
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4W (Standby), 3.0W (Max)
Inrush Current (Max)	N/A
Earth Leakage	N/A
IP Rating	IP20
IK Rating	N/A
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	Battery
8002430	LED Strip
AUM01270820001 LBLLED-CKIT-D2-NP	EM Driver Pack
8003062	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.