

Boxlite Exit, Recessed Wall Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Running Man, Single Sided



PRODUCT INFORMATION

Part Number	LBLLED-REC-WM-HVG-R
MIC	AUA01910160001
Description	Boxlite Exit, Recessed Wall Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Running Man, Single Sided
Construction	Body - Folded sheet steel. Powder coat (Dulux Pearl White) Trim Finish: Standard: Stainless Steel. Powder coat colours available. Specify when ordering.
Mounting	Recessed Wall
Dimensions L x W x D	350mm x 200mm (Trim) x 81mm (wall depth)
Wall Cut-out L x W x D	325mm x 180mm x 81mm
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Charging Method	Intelligent current limited constant voltage charger
Diffuser	Running Man (must specify diffuser combination)
Lamp(s)	6 x high intensity, low energy LED, surface mounted onto a replaceable lamp bar – 100,000 hour
Operating Voltage	240V
Power Consumption	1.7 Watts (Standby), 3.3 Watts (Max)
IP Rating	IP20
Operating Temperature	1° to 40°C
AS/NZS2293 Classification	N/A

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, Brkt
8002430	PCA:Duris P5 6 LED Strip.L10,#CT10166-D1
LBLLED-CKIT-NP	SMS, REC LED, Control Only, L10
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order