LBULK-D2

Bulklite IP65 Weatherproof Bulkhead Emergency, Surface Mount, L10 Nanophosphate, Non-maintained, DALI-2 Emergency



PRODUCT INFORMATION	
Part Number	LBULK-D2
MIC	AUS00000002301
Description	Bulklite IP65 Weatherproof Bulkhead Emergency, Surface Mount, L10 Nanophosphate, Non-maintained, DALI-2 Emergency
Construction	Base Material: Polycarbonate Diffuser Cover Material: Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	346mm x 132mm x 86mm
Weight	1.2kg
Operating Mode	Non-Maintained – Can be adjusted to Maintained via Jumper
Testing System	DALI-2
Battery	Lithium Nanophosphate 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	LED module, L80/B20, 100,000hrs @ Ta 30c 6500K, Ra>80
Diffuser	EXIT decals available separately
Operating Voltage	220-240V AC; 50Hz
Supply Current	0.054
Power Factor	0.399
Power Consumption	5.0Watts (Max), 4.0Watts (Maintained Standby), 0.7Watts (Standby)
Inrush Current (Peak/Duration)	TBC
Earth Leakage	TBC
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0˚C to 40˚C
AS2293 Classification	C0=D50, C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	**DESCRIPTION**
1530231	Battery
8050790	LED Panel
8002963	Emergency Driver
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.