



## LBULK-DALI

CLEVERTRONICS L10 BULKLITE  
WEATHERPROOF EMERGENCY LIGHT



PRODUCT INFORMATION	
Part Number	LBULK-DALI
MIC	UKS01220030002
Description	L10 Bulklite Weatherproof Emergency Light
Construction	Base Material: Polycarbonate Diffuser Cover Material: Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	346mm x 132mm x 86mm
Weight	1.2kg
Operating Mode	Non-Maintained – Can be adjusted to Maintained via Jumper
Testing System	DALI Registered
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO <sub>4</sub> ), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	LED module, L80/B20, 100,000hrs @ Ta 30c 6500K, Ra>80
Diffuser	EXIT decals available separately
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.7Watts (Standby), 4.0Watts (Maintained Standby), 5.0Watts (Max)
Total lumen output	395lm (Emergency) 395lm (Maintained)
Rated Emergency Duration	180 minutes
IP Rating	IP65
IK Rating	IK08
Operating temperature	0°C to 40°C
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li></ul>
Luminaire Classification	X 0 ADF 180
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530231	BATTERY:L10 3.3V 5AH. 200mm lead, no Brkt
8050790	LED: HWSUB: CT10754-D2 Petrus LED Strip - 2835 LP/L10
8002964	DRIVER: PCA: CT10142-L9 6C150 CTP DALI HV ZW UK 250mA Batt
8003060	PCA: New DALI #CT10629-Ax

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.