



LBULKM-SA-HVG

CLEVERTRONICS L10 BULKLITE
WEATHERPROOF EMERGENCY LIGHT



PRODUCT INFORMATION					
Part Number	LBULKM-SA-HVG				
MIC	UKS01820040001				
Description	L10 Bulklite Weatherproof Emergency Light, Maintained, Switched Active On/Off Control of LED's				
Construction	Base Material: Polycarbonate Diffuser Cover Material: Polycarbonate				
Mounting	Surface Mount				
Dimensions L x W x H	346mm x 132mm x 86mm				
Weight	1.2kg				
Operating Mode	Maintained – Switched Active On/Off Control of LED's				
Testing System	Zoneworks XT HIVE (RF)				
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent current limited constant voltage				
Lamp(s)	LED module, L80/B20, 100,000hrs @ Ta 30c 6500K, Ra>80				
Diffuser	EXIT decals available separately				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	0.7Watts (Standby), 4.0Watts (Maintained Standby), 5.0Watts (Max)				
Total lumen output	395lm (Emergency) 395lm (Maintained)				
Rated Emergency Duration	180 minutes				
IP Rating	IP65				
IK Rating	IK08				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault)				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>ADF</td><td>180</td></tr></table>	X	1	ADF	180
X	1	ADF	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530231	Battery
8050790	Emergent LED Panel
8002891	Emergency Driver Pack
8003330	HIVE Communication Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.