



## LBULKM-SA

CLEVERTRONICS L10 BULKLITE  
WEATHERPROOF EMERGENCY LIGHT



### PRODUCT INFORMATION

Part Number	LBULKM-SA				
MIC	UKS01320040001				
Description	L10 Bulklite Weatherproof Emergency Light, Maintained, Switched Active On/Off Control of LED's, Enabled with Clevertest Plus				
Construction	Base Material: Polycarbonate Diffuser Cover Material: Polycarbonate				
Mounting	Surface Mount				
Dimensions L x W x H	346mm x 132mm x 86mm				
Weight	1.2kg				
Operating Mode	Maintained – Switched Active On/Off Control of LED's				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent current limited constant voltage				
Lamp(s)	LED module, L80/B20, 100,000hrs @ Ta 30c 6500K, Ra>80				
Diffuser	EXIT decals available separately				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	0.4Watts (Standby), 3.7Watts (Maintained Standby), 4.7Watts (Max)				
Total lumen output	395lm (Emergency) 395lm (Maintained)				
Rated Emergency Duration	180 minutes				
IP Rating	IP65				
IK Rating	IK08				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li></ul> Battery short-circuit protection (charging will resume upon removal of fault)				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AD</td><td>180</td></tr></table>	X	1	AD	180
X	1	AD	180		
Conformity	BS EN 60598-2-22, BS 5266				

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	Battery
8050790	Emergent LED Panel
8002891	Emergency Driver Pack

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.