



LBULK

Bulkite IP65 Weatherproof Bulkhead Emergency, Surface Mount, L10 Nanophosphate, Non-maintained, Clevertest Plus



PRODUCT INFORMATION

Part Number	LBULK
MIC	UKS01320030002
Description	Bulkite IP65 Weatherproof Bulkhead Emergency, Surface Mount, L10 Nanophosphate, Non-maintained, Clevertest Plus
Construction	Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	346mm x 132mm x 86mm
Weight	1.2kg
Operating Mode	Maintained – Switched Active On/Off Control of LED's
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO ₄), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	LED module, L80/B20, 100,000hrs @ Ta 30c 6500K, Ra>80
Diffuser	EXIT decals available separately
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.4Watts (Standby), 3.7Watts (Maintained Standby), 4.7Watts (Max)
Supply Current	0.053A
Power Factor	0.395
Inrush Current (Peak/Duration)	19.4A / 134µs
Earth Leakage	N/A
Total lumen output	388lm (Emergency) 388lm (Maintained)
IP Rating	IP65
IK Rating	IK10
Operating temperature	0°C to 40°C
Rated Emergency Duration	180 minutes
Compliance Marking	
Luminaire Classification	X 0 AD 180
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533231	Battery
8003842	Emergency Driver
8050790	LED Assembly

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order