



LCFLED-D2

CLEVERTRONICS L10 CLEVERFIT EXIT, DALI-2



PRODUCT INFORMATION

Part Number	LCFLED-D2
MIC	AUA01211510001
Description	L10 Lithium Nanophosphate Cleverfit Emergency Exit, DALI-2
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	355mm x 215mm x 80mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.7 Watts (Standby), 4.5 Watts (Max)
Inrush Current (Max)	
Earth Leakage	
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D6.3 C90=D5
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	Battery
8002320	Driver
8002430	LED Strip
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.