



LCFLED-D2

Cleverfit Exit, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	LCFLED-D2			
MIC	UKA00000003901			
Description	Cleverfit Exit, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, All Pictograms, Single or Double Sided			
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover			
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided			
Dimensions L x W x H	355mm x 80mm x 215mm			
Weight	1.6kg			
Operating Mode	Maintained			
Testing System	DALI-2			
Battery Type & Manufacturer	Lithium Nanophosphate, 3.3V 2500mAh			
Charging Method	Intelligent Current Limited Constant Voltage			
Diffuser	All directional inserts included in the box			
Lamp(s)	6 x LED, 100,000 hours			
Operating Voltage	220-240V~ 50Hz			
Power Factor	0.446			
Supply Current	0.046A			
Power Consumption	2.4 Watts (Standby), 4.5 Watts (Max)			
Inrush Current (Peak/Duration)	12.5A/82µs			
Earth Leakage	N/A			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Luminaire Classification	X	1	AFG	180
Conformity	BS EN 60598-2-22, BS 5266			
Appliance Class	<input type="checkbox"/> Class II double insulated			
Compliance Marking	UKCA CE			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533090	Battery
8002710	LED Strip
8003803	Driver

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice