

## CLEVERTRONICS L10 CLEVERFIT EXIT (DALI)



### PRODUCT INFORMATION

Catalogue Number	LCFLED-DALI
MIC	UKA01210010002
Description	L10 Lithium Nanophosphate Cleverfit Emergency Exit
Construction	ABS body and Diffuser with Polycarbonate Clear Tamper proof Cover
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.7kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.7 Watts (Standby), 4.5 Watts (Max)

### PRODUCT INFORMATION

Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> <li>• Battery overvoltage &amp; overcurrent protection</li> <li>• Battery deep discharge protection</li> <li>• Supply voltage polarity reversal protection</li> <li>• Battery short-circuit protection (charging will resume upon removal of fault)</li> </ul>			
Luminaire Classification	X	1	AGF	180
Conformity	BS EN 60598-2-22, BS 5266			

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATTERY:L10 3.3V 2.5AH 390mm lead,noBrkt
8002710	PCA:DurisLED Strip Clvrft Pro CT10276-D3
8002337	PCA:LCFLED Driver CT10164-L6 6C70 CTP UK OWC
8003060	PCA: New DALI #CT10629-Ax

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.