



## LCFLED-HVG-BLK

Cleverfit Exit, Surface Mount, L10 Nanophosphate,  
Zoneworks XT Hive 2.4GHz, All Pictograms, Single or Double Sided



### PRODUCT INFORMATION

Part Number	LCFLED-HVG-BLK
MIC	AUA01910260001
Description	Cleverfit Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Black. All Pictograms, Single or Double Sided
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, Lifetime: >100,000hrs (AS/NZS2293.3 LSL=12Y/00M)
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby) 4.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D6.3 C90=D5
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	Battery
8002710	LED Strip
8002358	Driver
8003560	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.